Lunawood ThermoWood®



Document name: Declaration of performance - ThermoWood® Cladding and Paneling	Document nr. No 003	Page 1 of 2
Documented by: Jussi Vartiainen, Product Manager	Version 1	
Approved by: Arto Halonen, CEO	Original document: 20.12.2022	Version updated: 27.02.2023

Declaration of Performance No 003

1. Unique identification code of the product-type:

Thermally modified tongue & grooved massive wood board from Scots pine (Pinus sylvestris) for interior enduse applications. Thermal modification treatment class Thermo-D.

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

11 - 18 x 42 - 185 mm Wall and ceiling cladding for interior use.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Wooden wall and ceiling covering in interior end-use applications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Oy Lunawood Ltd Aleksanterinkatu 25A 15140 Lahti Tel. +358 44 797 5012 Web: www.lunawood.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

- does not exist

6. System or systems of assessment and verification of conctancy of performance of the construction product as set out in CPR, Annex V: AVCP system AVCP 4.

Notified body: Meža un koksnes produktu pētniecības un attīstības institūts (NB 2040)

Durability Class

Notified body: Georg-August-Universität Göttingen Wood Biology and Wood Produc ts (2014-110)

7. In case of the manufacturer's declaration concerning a construction product covered by a harmonised standard:

Lunawood ThermoWood®



Document name: Declaration of performance - ThermoWood® Cladding and Paneling	Document nr. No 003	Page 2 of 2
Documented by: Jussi Vartiainen, Product Manager	Version 1	
Approved by: Arto Halonen, CEO	Original document: 20.12.2022	Version updated: 27.02.2023

8. Declared performance:

Essential charasteristics	Pine (Pinus sylvestris)	Harmonized technical specification
Density:	420 kg/m³	
Reaction to fire class:	D-s2,d0	
Thermal conductivity:	0,09 W/(mK)	EN 14915:2013
Water vapour permeability:	60µ	
Emission of formaldehyde:	E1	
Content of pentachlorophenol:	NPD	
Release of other dangerous substances:	NPD	
Durability class:	Class 2 Thermo-D]
Use class:	Class 3 Thermo-D	

Signed for and on behalf of the manufacturer by:

Arto Halonen, CEO Lahti, 27 February 2023