Lunawood ThermoWood®



Document name: Declaration of performance - ThermoWood® Flooring	Document nr. No 005	Page 1 of 2
Documented by: Jussi Vartiainen, Product Management Director	Version 1	
Approved by: Arto Halonen, CEO	Original document: 20.12.2022	Version updated: 19.08.2024

Declaration of Performance No 005

1. Unique identification code of the product-type:

Thermally Thermally modified tongue & grooved massive flooring board from Scots Pine (Pinus sylvestris). Thermal modification treatment class Thermo-D

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

21-42 x 68-188 mm Wooden floor board.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Designed end use application: flooring in indoor use.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Oy Lunawood Ltd Aleksanterinkatu 25A 15140 Lahti Tel. +358 44 797 5012 Web: www.lunawood.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

- does not exist

6. System or systems of assessment and verification of conctancy of performance of the construction product as set out in CPR, Annex V: AVCP system

AVCP 3.

Durability Class

Notified body: Georg-August-Universität Göttingen Wood Biology and Wood Produc ts (2014-110)

7. In case of the manufacturer's declaration concerning a construction product covered by a harmonised standard:

The manufacturer has taken responsibility for initial type testing and implementation of FPC, in accordance

with AVCP level 3.

Lunawood ThermoWood®



Document name: Declaration of performance - ThermoWood® Flooring	Document nr. No 005	Page 2 of 2
Documented by: Jussi Vartiainen, Product Management Director	Version 1	
Approved by: Arto Halonen, CEO	Original document: 20.12.2022	Version updated: 19.08.2024

8. Declared performance:

Essential charasteristics	Pine (Pinus sylvestris)	Harmonized technical specification
Reaction to fire class:	NPD	
Density:	420 kg/m³	
Thermal conductivity:	0,09 W/(mK)	EN 14915:2013
Water vapour permeability:	60µ	
Emission of formaldehyde:	E1	
Content of pentachlorophenol:	NPD	
Release of other dangerous substances:	NPD	
Durability class:	Class 2 Thermo-D	
Use class:	Class 3 Thermo-D	

Signed for and on behalf of the manufacturer by:

Arto Halonen, CEO Lahti, 19 August 2024