Lunawood ThermoWood®



| Document name: Declaration of performance - ThermoWood® Decking | Document nr. No 013 | Page 1 of 2 |
|---|----------------------------------|--------------------------------|
| Documented by: Jussi Vartiainen, Product Management Director | Version 1 | |
| Approved by: Arto Halonen, CEO | Original document: 20.12.2022 | Version updated: 19.08.2024 |

Declaration of Performance No 013

1. Unique identification code of the product-type:

Thermally modified massive decking wood board from Scots pine (Pinus sylvestris) for exterior and interior enduse applications. Thermal modification treatment class Thermo-D.

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

26 - 40 x 92 - 185 mm Decking for exterior and interior use.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Wooden decking in exterior and interior end-use applications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Oy Lunawood Ltd Aleksanterinkatu 25A 15140 Lahti Tel. +358 44 797 5012 Web: www.lunawood.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

- does not exist

6. System or systems of assessment and verification of conctancy of performance of the construction product as set out in CPR, Annex V: AVCP system

AVCP 3.

Durability Class

Notified body: Georg-August-Universität Göttingen Wood Biology and Wood Produc ts (2014-110)

7. In case of the manufacturer's declaration concerning a construction product covered by a harmonised standard:

The manufacturer has taken responsibility for initial type testing and implementation of FPC, in accordance

with AVCP level 3.

Lunawood ThermoWood®



| Document name: Declaration of performance - ThermoWood® Decking | Document nr. No 013 | Page 2 of 2 |
|---|----------------------------------|--------------------------------|
| Documented by: Jussi Vartiainen, Product Management Director | Version 1 | |
| Approved by: Arto Halonen, CEO | Original document: 20.12.2022 | Version updated: 19.08.2024 |

8. Declared performance:

| Essential charasteristics | Pine (Pinus sylvestris) | Harmonized technical specification |
|--|-------------------------|------------------------------------|
| Reaction to fire class: | NPD | |
| Density: | 420 kg/m³ | |
| Thermal conductivity: | 0,09 W/(mK) | EN 14915:2013 |
| Water vapour permeability: | 60µ | |
| Emission of formaldehyde: | E1 | |
| Content of pentachlorophenol: | NPD | |
| Release of other dangerous substances: | NPD | |
| Durability class: | Class 2 Thermo-D | |
| Use class: | Class 3 Thermo-D | |

Signed for and on behalf of the manufacturer by:

Arto Halonen, CEO Lahti, 19 August 2024