## Lunawood ThermoWood®



Document name: Declaration of performance - ThermoWood® Decking	Document nr. No 014	Page 1 of 2
Documented by: Jussi Vartiainen, Product Management Director	Version 1	
Approved by: Arto Halonen, CEO	Original document: 20.12.2022	Version updated: 19.08.2024

## **Declaration of Performance No 014**

1. Unique identification code of the product-type:

Thermally modified massive decking wood board from Nordic Spruce (Picea abies) for exterior and interior enduse applications. Thermal modification treatment class Thermo-D.

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

26 - 32 x 140 - 166 mm

Decking for exterior and interior use.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Wooden decking in exterior and interior end-use applications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Oy Lunawood Ltd Aleksanterinkatu 25A 15140 Lahti Tel. +358 44 797 5012

Web: www.lunawood.com

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
- does not exist
- **6.** System or systems of assessment and verification of conctancy of performance of the construction product as set out in CPR, Annex V: AVCP system AVCP 3.

**Durability Class** 

Notified body: Georg-August-Universität Göttingen Wood Biology and Wood Produc ts (2014-110)

7. In case of the manufacturer's declaration concerning a construction product covered by a harmonised standard:

The manufacturer has taken responsibility for initial type testing and implementation of FPC, in accordance with AVCP level 3.

## Lunawood ThermoWood®



Document name: Declaration of performance - ThermoWood® Decking	Document nr. No 014	Page 2 of 2
Documented by: Jussi Vartiainen, Product Management Director	Version 1	
Approved by: Arto Halonen, CEO	Original document: 20.12.2022	Version updated: 19.08.2024

## 8. Declared performance:

Essential charasteristics	Spruce (Picea abies)	Harmonized technical specification
Reaction to fire class:	NPD	
Density:	420 kg/m³	
Thermal conductivity:	0,09 W/(mK)	EN 14915:2013
Water vapour permeability:	60µ	
Emission of formaldehyde:	E1	
Content of pentachlorophenol:	NPD	
Release of other dangerous substances:	NPD	
Durability class:	Class 2 Thermo-D	
Use class:	Class 3 Thermo-D	

Signed for and on behalf of the manufacturer by:

Arto Halonen, CEO Lahti, 19 August 2024