


KONEKTO N

DECKING CONNECTOR





OVERVIEW Length 74mm | Width 66mm | Height 10mm Dimensions: joint spacing 6.3 mm POM polyoxymethylene black UV and weather resistant Material: UNIA System screw: hardened stainless steel or A4 Stainless steel Concealed Sliding point fixation Fastening type: Dimensionally stable and modified Decking profile: wood species with side grooved profiled decking boards



The concealed decking connector **KONEKTO N** ensures a very easy, fast, and secure installation of modified, dimensionally stable wood species and composite decking boards with a side groove.

The decking board is clamped to the base plate by four flexible groove arms positioned in the side groove.

The flexible and permanently sprung groove arms automatically compensate for production-related irregularities in the decking board or its groove position.


As the screw head is housed in the base plate, it does not restrict the natural swelling and shrinking movements between the joints.

Two joint spacers ensure a consistent gap between the boards and can accommodate swelling and shrinking movements of up to 4 mm per board.

Swelling and shrinking movements are not transferred to the adjacent board - each board works independently, without a chain reaction across the entire decking area.

The substructure can be made of wood, wood-like materials, or aluminum.

KONEKTO N with UNIA1 PU Prod. No. 80 PCS



KONEKTO N with UNIA4	
PU	Prod. No.
80 PCS	034511001
240 PCS	034513001



SET-PACK

Each packaging contains the screws required for installation, UNIA system screws 4.8 x 34 mm and assembly instructions



BRANDING Custom branding upon request



System screw UNIA4 stainless steel A4 for terraces near coastal regions and around pools

